

Introduction

PELICAN-399 is a premium seawater RO antiscalant specially formulated to protect reverse osmosis membranes operating in high-salinity environments. It effectively prevents the formation of inorganic scale and minimizes particulate fouling, helping seawater desalination plants achieve consistent performance, higher water recovery, and longer membrane life.

It is suitable for use in Seawater Reverse Osmosis (SWRO), desalination and other high-salinity water treatment applications.



Highlights

- Excellent Scale Inhibition & Superior Membrane Protection
- Engineered to perform in high-salinity feed water
- Maintains clean membrane surfaces and consistent permeate quality
- Reliable Performance in High-Salinity Water
- Easy to Dose and Handle

Specification

Product Type	Seawater RO Antiscalant
Appearance	Colorless to White Liquid
Water Solubility	Completely Soluble
Solid Content	33–34% w/w
Specific Gravity	1.17–1.23
Application	Seawater / High-Salinity RO
Membrane Compatibility	RO / NF / UF Membranes
Form	Liquid



PELICAN-399

SEA WATER RO ANTISCALANT

Application and Dosage

PELICAN-399 should be dosed continuously into the RO feed-water line using a suitable chemical dosing pump.

Dosing Recommendations

In the useful dosage range of 5 –30 ppm, control of a wide range of inorganic scales at up to 100 x saturation values is possible. By monitoring the concentrate stream and trend charts, optimal dosage can be achieved for the control of scales including that from calcium carbonate, calcium sulfate, barium sulfate, strontium sulfate, iron hydroxide, aluminum hydroxide, and silica.

Storage

This product should be stored in original containers in cool and dry place, away from sources of heat, flame and direct sunlight.

Packaging

5, 10, 20 25, 30,50 Litre packaging Available